

PRODUCT INFORMATION



Firgelli Automations, 3888 Sound Way, Bellingham, WA 98226 USA

Tel, 1-360-450-5522

Fax 1 866 226-1649

Email sales@firgelliauto.com

www.FirgelliAuto.com

- Low noise design
- Enhanced corrosion resistance
- Aluminum outer and inner tube
- Zinc alloy housing
- Powder metal gears
- Lubrication for longer life
- Small compact Design
- Low Price




Specifications


Model	FA-PO-20-12-xx" (High Speed)	FA-PO-100-12-xx" (Standard Force)
Input Voltage	12 VDC	
Load Capacity	20 lbs	100lbs
Static Load	2 x max load capacity	
Stroke Length	2" to 12"	
Speed at No Load	2"/sec (50mm/s)	½"/sec (12mm/sec)
Feedback	10K ohm 3 wires Potentiometer	
Clevis Ends	6.3mm diameter	
Screw	ACME screw	
Gear Ratio	5:1	20:1
Duty Cycle	20%	
Operation Temperature Range	-26°C~65°C (-15°F~150°F)	
Limit Switch	Built-in (Factory Preset) Not movable	
IP Grade	IP54 (dust and splash proof)	

PRODUCT INFORMATION

LOAD/SPEED




LOAD/CURRENT



PRODUCT INFORMATION

Dimensions:



Wiring:


Red +12vdc (actuator extends,
Black gnd reverse polarity to retract)

Feedback wiring if required:

White - Potentiometer reference

Yellow - Potentiometer reference

Blue - Potentiometer wiper (position signal)



- This model actuator uses Fircelli Automations MB1 Brackets on both ends of the actuator.
- Visit http://www.fircelliauto.com/product_info.php?cPath=70&products_id=54 for more details

Please visit our website for latest prices and to purchase
www.FircelliAuto.com